

DIESEL AIR COMPRESSORS | AC-185 / AC-212

Trailer-mounted diesel air compressors for construction, oil field, and industrial applications. EPA Tier 4 Final compliant. Both models feature single stage oil-injected screw compression and are designed for continuous duty in remote and demanding environments.

Specification	AC-185	AC-212
CFM Output	185 CFM	212 CFM
Pressure Rating	116 PSI	116 PSI
Engine (Option 1)	Cummins QSF2.8	Cummins QSF2.8
Engine Power	37 kW	55 kW
Engine (Option 2)	--	Yanmar 4TNV98CT
Engine Power (Opt. 2)	--	53.7 kW
Emission Standard	EPA Tier 4 Final	EPA Tier 4 Final
Rated Speed	2,500 RPM	2,500 RPM
Compression Stages	Single stage	Single stage
Air Outlets	1x G1", 1x G3/4"	3x G1", 1x G3/4"
Supply Air Temp	≤ 90°C	≤ 90°C
Fuel Tank	72 L	92 L
Equipment Weight	1,050 kg	1,400 - 1,500 kg
Mount	Trailer, 2 wheel	Trailer, 2 wheel
Dimensions L	2,400 mm	1,880 - 2,180 mm
Dimensions W	1,650 mm	1,630 mm
Dimensions H	1,600 mm	1,800 mm

COMMON FEATURES	APPLICATIONS
EPA Tier 4 Final compliant engines Single stage oil-injected screw compression Trailer mounted for easy towing and mobility Integrated fuel tank Multiple air outlet configurations Supply air temperature ≤ 90°C Suitable for continuous duty cycles	Construction and demolition Sandblasting and surface preparation Pneumatic tool operation Pipeline testing and purging Oil field and well services Mining and drilling operations Remote site power and air supply