

Lynx | TH-519 ★ Most Popular

Capacity 5,512 lbs | Max Height 19.7 ft | Max Reach 7.1 ft

LIFTING		DIMENSIONS	
Rated Capacity	5,512 lbs (2,500 kg)	Machine Weight	12,787 lbs (5,800 kg)
Max Lifting Height	19.7 ft (6.0 m)	Overall Length	13.1 ft (4.0 m)
Max Outreach	7.1 ft (2.16 m)	Overall Width / Height	6.6 ft (2.02 m) / 6.7 ft (2.05 m)
PERFORMANCE		Wheelbase	9.2 ft (2.8 m)
Max Travel Speed	21.7 mph (35 km/h)	Ground Clearance	9.1 in (0.23 m)
Steering Modes	2WD / 4WD / Crab	Turning Radius	14.8 ft (4.5 m)
POWERTRAIN & CAPACITIES			
Engine	Cummins / FPT EPA 4	Fuel Tank	21.1 gal (80 L)
Transmission	Torque Converter 4F/4R	Hydraulic Tank	44.9 gal (170 L)
Tires	12-16.5 Pneumatic	Hydraulic Flow	85 L/min @ 220 bar

TH-623

Capacity 6,614 lbs | Max Height 23.0 ft | Max Reach 10.5 ft

LIFTING		DIMENSIONS	
Rated Capacity	6,614 lbs (3,000 kg)	Machine Weight	16,755 lbs (7,600 kg)
Max Lifting Height	23.0 ft (7.0 m)	Overall Length	15.3 ft (4.65 m)
Max Outreach	10.5 ft (3.2 m)	Overall Width / Height	N/A / 8.4 ft (2.55 m)
PERFORMANCE		Wheelbase	10.3 ft (3.15 m)
Max Travel Speed	21.7 mph (35 km/h)	Ground Clearance	13.8 in (0.35 m)
Steering Modes	2WD / 4WD / Crab	Turning Radius	13.9 ft (4.25 m)
POWERTRAIN & CAPACITIES			
Engine	Cummins / FPT EPA 4	Fuel Tank	51.5 gal (195 L)
Transmission	Torque Converter 4F/4R	Hydraulic Tank	44.9 gal (170 L)
Tires	16/70-20 Pneumatic	Hydraulic Flow	120 L/min

TH-723

Capacity 7,716 lbs | Max Height 23.0 ft | Max Reach 10.5 ft

LIFTING		DIMENSIONS	
Rated Capacity	7,716 lbs (3,500 kg)	Machine Weight	16,755 lbs (7,600 kg)
Max Lifting Height	23.0 ft (7.0 m)	Overall Length	15.3 ft (4.65 m)
Max Outreach	10.5 ft (3.2 m)	Overall Width / Height	7.2 ft (2.2 m) / 8.4 ft (2.55 m)
PERFORMANCE		Wheelbase	10.3 ft (3.15 m)
Max Travel Speed	21.7 mph (35 km/h)	Ground Clearance	13.8 in (0.35 m)
Steering Modes	2WD / 4WD / Crab	Turning Radius	13.9 ft (4.25 m)
POWERTRAIN & CAPACITIES			
Engine	Cummins / FPT EPA 4	Fuel Tank	51.5 gal (195 L)
Transmission	Torque Converter 4F/4R	Hydraulic Tank	44.9 gal (170 L)
Tires	16/70-20 Pneumatic	Hydraulic Flow	120 L/min

TH-733

Capacity 7,716 lbs | Max Height 32.8 ft | Max Reach 20.0 ft

LIFTING		DIMENSIONS	
Rated Capacity	7,716 lbs (3,500 kg)	Machine Weight	20,944 lbs (9,500 kg)
Max Lifting Height	32.8 ft (10.0 m)	Overall Length	19.0 ft (5.8 m)
Max Outreach	20.0 ft (6.1 m)	Overall Width / Height	7.2 ft (2.2 m) / 8.4 ft (2.55 m)
PERFORMANCE		Wheelbase	10.3 ft (3.15 m)
Max Travel Speed	21.7 mph (35 km/h)	Ground Clearance	13.8 in (0.35 m)
Steering Modes	2WD / 4WD / Crab	Turning Radius	13.9 ft (4.25 m)
POWERTRAIN & CAPACITIES			
Engine	Cummins / FPT EPA 4	Fuel Tank	51.5 gal (195 L)
Transmission	Torque Converter 4F/4R	Hydraulic Tank	44.9 gal (170 L)
Tires	16/70-20 Pneumatic	Hydraulic Flow	120 L/min

TH-739

Capacity 7,716 lbs | Max Height 39.4 ft | Max Reach 24.9 ft

LIFTING		DIMENSIONS	
Rated Capacity	7,716 lbs (3,500 kg)	Machine Weight	22,487 lbs (10,200 kg)
Max Lifting Height	39.4 ft (12.0 m)	Overall Length	21.7 ft (6.6 m)
Max Outreach	24.9 ft (7.6 m)	Overall Width / Height	7.2 ft (2.2 m) / 8.5 ft (2.60 m)
PERFORMANCE		Wheelbase	10.3 ft (3.15 m)
Max Travel Speed	21.7 mph (35 km/h)	Ground Clearance	15.7 in (0.4 m)
Steering Modes	2WD / 4WD / Crab	Turning Radius	13.9 ft (4.25 m)
POWERTRAIN & CAPACITIES			
Engine	Cummins / FPT EPA 4	Fuel Tank	51.5 gal (195 L)
Transmission	Torque Converter 4F/4R	Hydraulic Tank	44.9 gal (170 L)
Tires	16/70-24 Pneumatic	Hydraulic Flow	120 L/min

TH-823

Capacity 8,818 lbs | Max Height 23.0 ft | Max Reach 10.5 ft

LIFTING		DIMENSIONS	
Rated Capacity	8,818 lbs (4,000 kg)	Machine Weight	17,857 lbs (8,100 kg)
Max Lifting Height	23.0 ft (7.0 m)	Overall Length	15.3 ft (4.65 m)
Max Outreach	10.5 ft (3.2 m)	Overall Width / Height	7.2 ft (2.2 m) / 8.4 ft (2.55 m)
PERFORMANCE		Wheelbase	10.3 ft (3.15 m)
Max Travel Speed	21.7 mph (35 km/h)	Ground Clearance	13.8 in (0.35 m)
Steering Modes	2WD / 4WD / Crab	Turning Radius	13.9 ft (4.25 m)
POWERTRAIN & CAPACITIES			
Engine	Cummins / FPT EPA 4	Fuel Tank	51.5 gal (195 L)
Transmission	Torque Converter 2F/2R	Hydraulic Tank	44.9 gal (170 L)
Tires	16/70-20 Pneumatic	Hydraulic Flow	150 L/min

TH-835

Capacity 8,818 lbs | Max Height 34.8 ft | Max Reach 20.0 ft

LIFTING		DIMENSIONS	
Rated Capacity	8,818 lbs (4,000 kg)	Machine Weight	22,707 lbs (10,300 kg)
Max Lifting Height	34.8 ft (10.6 m)	Overall Length	19.0 ft (5.8 m)
Max Outreach	20.0 ft (6.1 m)	Overall Width / Height	7.2 ft (2.2 m) / 8.4 ft (2.55 m)
PERFORMANCE		Wheelbase	10.3 ft (3.15 m)
Max Travel Speed	21.7 mph (35 km/h)	Ground Clearance	13.8 in (0.35 m)
Steering Modes	2WD / 4WD / Crab	Turning Radius	13.9 ft (4.25 m)
POWERTRAIN & CAPACITIES			
Engine	Cummins / FPT EPA 4	Fuel Tank	51.5 gal (195 L)
Transmission	Torque Converter 4F/4R	Hydraulic Tank	44.9 gal (170 L)
Tires	400/70-24 Tubeless	Hydraulic Flow	150 L/min

TH-845

Capacity 8,818 lbs | Max Height 45.3 ft | Max Reach 23.0 ft

LIFTING		DIMENSIONS	
Rated Capacity	8,818 lbs (4,000 kg)	Machine Weight	28,660 lbs (13,000 kg)
Max Lifting Height	45.3 ft (13.8 m)	Overall Length	21.0 ft (6.4 m)
Max Outreach	23.0 ft (7.0 m)	Overall Width / Height	7.7 ft (2.35 m) / 8.4 ft (2.55 m)
PERFORMANCE		Wheelbase	11.8 ft (3.6 m)
Max Travel Speed	24.9 mph (40 km/h)	Ground Clearance	15.0 in (0.38 m)
Steering Modes	2WD / 4WD / Crab	Turning Radius	13.5 ft (4.1 m)
POWERTRAIN & CAPACITIES			
Engine	Cummins / FPT EPA 4	Fuel Tank	51.5 gal (195 L)
Transmission	Torque Converter 4F/4R	Hydraulic Tank	44.9 gal (170 L)
Tires	440/80-24 Tubeless	Hydraulic Flow	150 L/min

Leopard | TH-858 ★ Most Popular

Capacity 8,818 lbs | Max Height 57.7 ft | Max Reach 42.0 ft

LIFTING		DIMENSIONS	
Rated Capacity	8,818 lbs (4,000 kg)	Machine Weight	6,614 lbs (3,000 kg)
Max Lifting Height	57.7 ft (17.6 m)	Overall Length	21.0 ft (6.4 m)
Max Outreach	42.0 ft (12.8 m)	Overall Width / Height	7.7 ft (2.35 m) / 8.4 ft (2.55 m)
PERFORMANCE		Wheelbase	11.8 ft (3.6 m)
Max Travel Speed	24.9 mph (40 km/h)	Ground Clearance	15.0 in (0.38 m)
Steering Modes	2WD / 4WD / Crab	Turning Radius	13.5 ft (4.1 m)
POWERTRAIN & CAPACITIES			
Engine	Cummins / FPT EPA 4	Fuel Tank	51.5 gal (195 L)
Transmission	Torque Converter 4F/4R	Hydraulic Tank	44.9 gal (170 L)
Tires	440/80-24 Tubeless	Hydraulic Flow	150 L/min

TH-1132

Capacity 11,023 lbs | Max Height 32.2 ft | Max Reach 16.4 ft

LIFTING		DIMENSIONS	
Rated Capacity	11,023 lbs (5,000 kg)	Machine Weight	28,219 lbs (12,800 kg)
Max Lifting Height	32.2 ft (9.8 m)	Overall Length	21.0 ft (6.4 m)
Max Outreach	16.4 ft (5.0 m)	Overall Width / Height	7.7 ft (2.35 m) / 8.4 ft (2.55 m)
PERFORMANCE		Wheelbase	11.8 ft (3.6 m)
Max Travel Speed	24.9 mph (40 km/h)	Ground Clearance	15.0 in (0.38 m)
Steering Modes	2WD / 4WD / Crab	Turning Radius	13.5 ft (4.1 m)
POWERTRAIN & CAPACITIES			
Engine	Cummins / FPT EPA 4	Fuel Tank	51.5 gal (195 L)
Transmission	Torque Converter 4F/4R	Hydraulic Tank	44.9 gal (170 L)
Tires	16/70-24 Semi-Solid	Hydraulic Flow	150 L/min

TH-1145

Capacity 11,023 lbs | Max Height 45.3 ft | Max Reach 26.2 ft

LIFTING		DIMENSIONS	
Rated Capacity	11,023 lbs (5,000 kg)	Machine Weight	29,982 lbs (13,600 kg)
Max Lifting Height	45.3 ft (13.8 m)	Overall Length	21.7 ft (6.6 m)
Max Outreach	26.2 ft (8.0 m)	Overall Width / Height	7.7 ft (2.35 m) / 8.4 ft (2.55 m)
PERFORMANCE		Wheelbase	11.8 ft (3.6 m)
Max Travel Speed	24.9 mph (40 km/h)	Ground Clearance	15.0 in (0.38 m)
Steering Modes	2WD / 4WD / Crab	Turning Radius	13.5 ft (4.1 m)
POWERTRAIN & CAPACITIES			
Engine	Cummins / FPT EPA 4	Fuel Tank	51.5 gal (195 L)
Transmission	Torque Converter 4F/4R	Hydraulic Tank	50.2 gal (190 L)
Tires	440/80-24 Tubeless	Hydraulic Flow	150 L/min

Lion | TH-1158 ★ Most Popular

Capacity 11,023 lbs | Max Height 57.6 ft | Max Reach 36.7 ft

LIFTING		DIMENSIONS	
Rated Capacity	11,023 lbs (5,000 kg)	Machine Weight	31,086 lbs (14,100 kg)
Max Lifting Height	57.6 ft (17.55 m)	Overall Length	21.7 ft (6.6 m)
Max Outreach	36.7 ft (11.2 m)	Overall Width / Height	7.7 ft (2.35 m) / 8.7 ft (2.65 m)
PERFORMANCE		Wheelbase	11.8 ft (3.6 m)
Max Travel Speed	24.9 mph (40 km/h)	Ground Clearance	15.0 in (0.38 m)
Steering Modes	2WD / 4WD / Crab	Turning Radius	13.5 ft (4.1 m)
POWERTRAIN & CAPACITIES			
Engine	Cummins / FPT EPA 4	Fuel Tank	51.5 gal (195 L)
Transmission	Torque Converter 4F/4R	Hydraulic Tank	50.2 gal (190 L)
Tires	440/80-24 Tubeless	Hydraulic Flow	150 L/min

TH-1358

Capacity 13,228 lbs | Max Height 57.7 ft | Max Reach 39.4 ft

LIFTING		DIMENSIONS	
Rated Capacity	13,228 lbs (6,000 kg)	Machine Weight	37,479 lbs (17,000 kg)
Max Lifting Height	57.7 ft (17.6 m)	Overall Length	22.6 ft (6.9 m)
Max Outreach	39.4 ft (12.0 m)	Overall Width / Height	8.9 ft (2.7 m) / 9.1 ft (2.76 m)
PERFORMANCE		Wheelbase	11.8 ft (3.6 m)
Max Travel Speed	24.9 mph (40 km/h)	Ground Clearance	19.7 in (0.50 m)
Steering Modes	2WD / 4WD / Crab	Turning Radius	13.5 ft (4.1 m)
POWERTRAIN & CAPACITIES			
Engine	Cummins / FPT EPA 4	Fuel Tank	51.5 gal (195 L)
Transmission	Torque Converter 4F/4R	Hydraulic Tank	44.9 gal (170 L)
Tires	17.5-25 Tubeless	Hydraulic Flow	180 L/min

TH-1558

Capacity 15,432 lbs | Max Height 57.7 ft | Max Reach 39.4 ft

LIFTING		DIMENSIONS	
Rated Capacity	15,432 lbs (7,000 kg)	Machine Weight	38,581 lbs (17,500 kg)
Max Lifting Height	57.7 ft (17.6 m)	Overall Length	27.2 ft (8.3 m)
Max Outreach	39.4 ft (12.0 m)	Overall Width / Height	8.5 ft (2.6 m) / 9.4 ft (2.85 m)
PERFORMANCE		Wheelbase	11.8 ft (3.6 m)
Max Travel Speed	24.9 mph (40 km/h)	Ground Clearance	19.7 in (0.50 m)
Steering Modes	2WD / 4WD / Crab	Turning Radius	13.5 ft (4.1 m)
POWERTRAIN & CAPACITIES			
Engine	Cummins / FPT EPA 4	Fuel Tank	34.3 gal (130 L)
Transmission	Torque Converter 4F/4R	Hydraulic Tank	44.9 gal (170 L)
Tires	17.5-25 Tubeless	Hydraulic Flow	180 L/min