

TL254 - 25hp ★ Featured

Engine: Diesel 3-cyl | Drive: 4x4 | Gearbox: 8+2 Shift

DIMENSIONS & WEIGHT		PERFORMANCE	
Machine Weight	3,086 lbs (1,400 kg)	PTO Speed	540/760 rpm
Overall Length	10.6 ft (3,220 mm)	Max Lift (610mm)	929 lbs (4.13 kN) at 610mm
Overall Width	4.8 ft (1,455 mm)	Min Turn Radius	7.5 ft (2.3 m) braking / 9.8 ft (3.0 m)
Overall Height	5.9 ft (1,800 mm)	Suspension	3-point type 1
Wheelbase	5.7 ft (1,730 mm)	Ground Clearance	11.4 in (290 mm)
TIRES			
Front Tires	6.0-16 / 6.5-16 / 7.5-16	Rear Tires	9.5-24 / 11.2-24 / 12.4-24

TL304 - 30hp

Engine: Diesel 3-cyl | Drive: 4x4 | Gearbox: 8+2 Shift

DIMENSIONS & WEIGHT		PERFORMANCE	
Machine Weight	3,086 lbs (1,400 kg)	PTO Speed	540/760 rpm
Overall Length	10.6 ft (3,220 mm)	Max Lift (610mm)	1,115 lbs (4.96 kN) at 610mm
Overall Width	4.8 ft (1,455 mm)	Min Turn Radius	7.5 ft (2.3 m) braking / 9.8 ft (3.0 m)
Overall Height	7.3 ft (2,225 mm)	Suspension	3-point type 1
Wheelbase	5.7 ft (1,730 mm)	Ground Clearance	11.4 in (290 mm)
TIRES			
Front Tires	6.00-16 / 6.5-16 / 7.5-16	Rear Tires	9.50-24 / 11.2-24 / 12.4-24

TL454 - 45hp ★ Featured

Engine: Diesel 4-cyl | Drive: 4x4 | Gearbox: 8+2 Shift

DIMENSIONS & WEIGHT		PERFORMANCE	
Machine Weight	3,968 lbs (1,800 kg)	PTO Speed	540/760 rpm
Overall Length	10.6 ft (3,220 mm)	Max Lift (610mm)	1,686 lbs (7.5 kN) at 610mm
Overall Width	4.9 ft (1,500 mm)	Min Turn Radius	11.5 ft (3.5 m) braking / 13.1 ft (4.0 m)
Overall Height	8.0 ft (2,450 mm)	Suspension	3-point type 1
Wheelbase	6.2 ft (1,885 mm)	Ground Clearance	11.6 in (295 mm)
TIRES			
Front Tires	6.00-16 / 6.5-16 / 7.5-16	Rear Tires	9.5-24 / 11.2-24 / 12.4-24

TL504 - 50hp

Engine: Diesel 4-cyl | Drive: 4x4 | Gearbox: 8+8 Shuttle Shift

DIMENSIONS & WEIGHT		PERFORMANCE	
Machine Weight	3,748-4,630 lbs (1,700-2,100 kg)	PTO Speed	540/760 rpm
Overall Length	11.7 ft (3,560 mm)	Max Lift (610mm)	1,979 lbs (8.8 kN) at 610mm
Overall Width	5.4 ft (1,650 mm)	Min Turn Radius	9.3 ft (2.85 m) braking / 10.3 ft (3.15 m)
Overall Height	8.4 ft (2,550 mm)	Suspension	3-point type 1 or 2
Wheelbase	6.4 ft (1,965 mm)	Ground Clearance	13.0 in (330 mm)
TIRES			
Front Tires	6.5-16 / 7.5-16 / 8.3-20	Rear Tires	11.2-24 / 12.4-24 / 12.4-28

TL604 - 60hp

Engine: Diesel 4-cyl | Drive: 4x4 | Gearbox: 8+8 Shuttle Shift

DIMENSIONS & WEIGHT		PERFORMANCE	
Machine Weight	3,748-4,630 lbs (1,700-2,100 kg)	PTO Speed	540/760 rpm
Overall Length	11.7 ft (3,560 mm)	Max Lift (610mm)	2,248 lbs (10.0 kN) at 610mm
Overall Width	5.4 ft (1,650 mm)	Min Turn Radius	9.3 ft (2.85 m) braking / 10.3 ft (3.15 m)
Overall Height	8.4 ft (2,550 mm)	Suspension	3-point type 1 or 2
Wheelbase	6.4 ft (1,965 mm)	Ground Clearance	13.0 in (330 mm)
TIRES			
Front Tires	6.5-16 / 7.5-16 / 8.3-20	Rear Tires	11.2-24 / 12.4-24 / 12.4-28

TL704 - 70hp ★ Featured

Engine: Diesel 4-cyl | Drive: 4x4 | Gearbox: 8F+8R Shuttle Shift

DIMENSIONS & WEIGHT		PERFORMANCE	
Machine Weight	3,748-4,630 lbs (1,700-2,100 kg)	PTO Speed	540/760 rpm
Overall Length	11.7 ft (3,560 mm)	Max Lift (610mm)	2,439 lbs (10.85 kN) at 610mm
Overall Width	5.4 ft (1,650 mm)	Min Turn Radius	9.3 ft (2.85 m) braking / 10.3 ft (3.15 m)
Overall Height	8.4 ft (2,550 mm)	Suspension	3-point type 1 or 2
Wheelbase	6.4 ft (1,965 mm)	Ground Clearance	13.0 in (330 mm)
TIRES			
Front Tires	6.5-16 / 7.5-16 / 8.3-20	Rear Tires	11.2-24 / 12.4-24 / 12.4-28

TL804B - 80hp

Engine: Diesel 4-cyl | Drive: 4x4 | Gearbox: 12F+12R Shuttle Shift

DIMENSIONS & WEIGHT		PERFORMANCE	
Machine Weight	6,614 lbs (3,000 kg)	PTO Speed	540/760 rpm
Overall Length	12.8 ft (3,910 mm)	Max Lift (610mm)	≥ 3,197 lbs (14.2 kN) at 610mm
Overall Width	6.1 ft (1,850 mm)	Min Turn Radius	≤ 15.1 ft (4.6 m)
Overall Height	9.0 ft (2,750 mm)	Suspension	3-point type 1
Wheelbase	6.7 ft (2,040 mm)	Ground Clearance	15.7 in (400 mm)
TIRES			
Front Tires	9.5-24	Rear Tires	14.9-30

TL904B - 90hp

Engine: Diesel 4-cyl | Drive: 4x4 | Gearbox: 12F+12R Shuttle Shift

DIMENSIONS & WEIGHT		PERFORMANCE	
Machine Weight	6,614 lbs (3,000 kg)	PTO Speed	540/760 rpm
Overall Length	12.8 ft (3,910 mm)	Max Lift (610mm)	≥ 3,600 lbs (16.0 kN) at 610mm
Overall Width	6.1 ft (1,850 mm)	Min Turn Radius	≤ 15.1 ft (4.6 m)
Overall Height	9.0 ft (2,750 mm)	Suspension	3-point type 2
Wheelbase	6.7 ft (2,040 mm)	Ground Clearance	15.7 in (400 mm)
TIRES			
Front Tires	9.5-24	Rear Tires	14.9-30

TL1004 - 100hp ★ Featured

Engine: Diesel 4-cyl | Drive: 4x4 | Gearbox: 12F+12R Shuttle Shift

DIMENSIONS & WEIGHT		PERFORMANCE	
Machine Weight	6,614 lbs (3,000 kg)	PTO Speed	540/760 rpm
Overall Length	12.8 ft (3,910 mm)	Max Lift (610mm)	≥ 3,979 lbs (17.7 kN) at 610mm
Overall Width	6.1 ft (1,850 mm)	Min Turn Radius	≤ 15.1 ft (4.6 m)
Overall Height	9.0 ft (2,750 mm)	Suspension	3-point type 2
Wheelbase	6.7 ft (2,040 mm)	Ground Clearance	15.7 in (400 mm)
TIRES			
Front Tires	9.5-24	Rear Tires	14.9-30

110hp - 110hp

Engine: Diesel 4-cyl | Drive: 4x4 | Gearbox: 16F+8R Creeper Shift

DIMENSIONS & WEIGHT		PERFORMANCE	
Machine Weight	9,590 lbs (4,350 kg)	PTO Speed	540/1000 rpm
Overall Length	15.6 ft (4,750 mm)	Max Lift (610mm)	≥ 4,948 lbs (22.0 kN) at 610mm
Overall Width	7.5 ft (2,300 mm)	Min Turn Radius	≤ 15.7 ft (4.8 m)
Overall Height	9.8 ft (3,000 mm)	Suspension	3-point type 2
Wheelbase	7.2-8.4 ft (2,195-2,560 mm)	Ground Clearance	15.7 in (400 mm)
TIRES			
Front Tires	12.4-24	Rear Tires	16.9-34

120hp - 120hp

Engine: Diesel 6-cyl | Drive: 4x4 | Gearbox: 16F+8R Creeper Shift

DIMENSIONS & WEIGHT		PERFORMANCE	
Machine Weight	9,590 lbs (4,350 kg)	PTO Speed	540/1000 rpm
Overall Length	15.6 ft (4,750 mm)	Max Lift (610mm)	≥ 5,621 lbs (25.0 kN) at 610mm
Overall Width	7.5 ft (2,300 mm)	Min Turn Radius	≤ 15.7 ft (4.8 m)
Overall Height	9.8 ft (3,000 mm)	Suspension	3-point type 2
Wheelbase	7.2-8.4 ft (2,195-2,560 mm)	Ground Clearance	15.7 in (400 mm)
TIRES			
Front Tires	12.4-24	Rear Tires	16.9-34

130hp - 130hp

Engine: Diesel 6-cyl | Drive: 4x4 | Gearbox: 16F+8R Creeper Shift

DIMENSIONS & WEIGHT		PERFORMANCE	
Machine Weight	9,590 lbs (4,350 kg)	PTO Speed	540/1000 rpm
Overall Length	15.6 ft (4,750 mm)	Max Lift (610mm)	≥ 6,069 lbs (27.0 kN) at 610mm
Overall Width	7.5 ft (2,300 mm)	Min Turn Radius	≤ 15.7 ft (4.8 m)
Overall Height	9.8 ft (3,000 mm)	Suspension	3-point type 2
Wheelbase	7.2-8.4 ft (2,195-2,560 mm)	Ground Clearance	15.7 in (400 mm)
TIRES			
Front Tires	12.4-24	Rear Tires	16.9-34

140hp - 140hp

Engine: Diesel 6-cyl | Drive: 4x4 | Gearbox: 16F+8R Creeper Shift

DIMENSIONS & WEIGHT		PERFORMANCE	
Machine Weight	9,590 lbs (4,350 kg)	PTO Speed	540/1000 rpm
Overall Length	15.6 ft (4,750 mm)	Max Lift (610mm)	≥ 6,518 lbs (29.0 kN) at 610mm
Overall Width	7.5 ft (2,300 mm)	Min Turn Radius	≤ 15.7 ft (4.8 m)
Overall Height	9.8 ft (3,000 mm)	Suspension	3-point type 2
Wheelbase	7.2-8.4 ft (2,195-2,560 mm)	Ground Clearance	15.7 in (400 mm)
TIRES			
Front Tires	12.4-24	Rear Tires	16.9-34

TL1504F - 150hp

Engine: Diesel 6-cyl | Drive: 4x4 | Gearbox: 16F+8R Shift

DIMENSIONS & WEIGHT		PERFORMANCE	
Machine Weight	11,464 lbs (5,200 kg)	PTO Speed	540/1000 rpm
Overall Length	16.6 ft (5,050 mm)	Max Lift (610mm)	5,952 lbs (26.5 kN) at 610mm
Overall Width	7.2 ft (2,180 mm)	Min Turn Radius	≤ 14.1 ft (4.3 m) braking / ≤ 15.7 ft (4.8 m)
Overall Height	10.2 ft (3,120 mm)	Suspension	3-point type 3
Wheelbase	8.3 ft (2,520 mm)	Ground Clearance	16.7 in (425 mm)
TIRES			
Front Tires	14.9-26	Rear Tires	18.4-38

TL1604F - 160hp

Engine: Diesel 6-cyl | Drive: 4x4 | Gearbox: 16F+8R Shift

DIMENSIONS & WEIGHT		PERFORMANCE	
Machine Weight	13,999 lbs (6,350 kg)	PTO Speed	540/1000 rpm
Overall Length	16.6 ft (5,050 mm)	Max Lift (610mm)	6,360 lbs (28.3 kN) at 610mm
Overall Width	7.5 ft (2,300 mm)	Min Turn Radius	≤ 14.1 ft (4.3 m) braking / ≤ 15.7 ft (4.8 m)
Overall Height	9.8 ft (3,000 mm)	Suspension	3-point type 3
Wheelbase	8.3 ft (2,520 mm)	Ground Clearance	16.7 in (425 mm)
TIRES			
Front Tires	14.9-26	Rear Tires	18.4-38

TL1804F - 180hp

Engine: Diesel 6-cyl | Drive: 4x4 | Gearbox: 16F+8R Shift

DIMENSIONS & WEIGHT		PERFORMANCE	
Machine Weight	13,999 lbs (6,350 kg)	PTO Speed	540/1000 rpm
Overall Length	16.6 ft (5,050 mm)	Max Lift (610mm)	7,143 lbs (31.8 kN) at 610mm
Overall Width	7.5 ft (2,300 mm)	Min Turn Radius	≤ 14.1 ft (4.3 m) braking / ≤ 15.7 ft (4.8 m)
Overall Height	9.8 ft (3,000 mm)	Suspension	3-point type 3
Wheelbase	8.3 ft (2,520 mm)	Ground Clearance	16.7 in (425 mm)
TIRES			
Front Tires	14.9-26	Rear Tires	18.4-38

TL2004G - 200hp

Engine: Diesel 6-cyl | Drive: 4x4 | Gearbox: 16F+8R Shift

DIMENSIONS & WEIGHT		PERFORMANCE	
Machine Weight	13,999 lbs (6,350 kg)	PTO Speed	540/1000 rpm
Overall Length	17.6 ft (5,350 mm)	Max Lift (610mm)	7,716 lbs (35.0 kN) at 610mm
Overall Width	7.2 ft (2,200 mm)	Min Turn Radius	≤ 20.3 ft (6.2 m) braking / ≤ 23.0 ft (7.0 m)
Overall Height	10.8 ft (3,300 mm)	Suspension	3-point type 3
Wheelbase	8.8 ft (2,668 mm)	Ground Clearance	16.7 in (425 mm)
TIRES			
Front Tires	16.9-28	Rear Tires	20.8-38

TL2404G - 240hp

Engine: Diesel 6-cyl | Drive: 4x4 | Gearbox: 16F+8R Shift

DIMENSIONS & WEIGHT		PERFORMANCE	
Machine Weight	16,094 lbs (7,320 kg)	PTO Speed	540/1000 rpm
Overall Length	17.6 ft (5,350 mm)	Max Lift (610mm)	9,259 lbs (42.0 kN) at 610mm
Overall Width	7.2 ft (2,200 mm)	Min Turn Radius	≤ 20.3 ft (6.2 m) braking / ≤ 23.0 ft (7.0 m)
Overall Height	10.8 ft (3,300 mm)	Suspension	3-point type 3
Wheelbase	8.8 ft (2,668 mm)	Ground Clearance	16.7 in (425 mm)
TIRES			
Front Tires	16.9-28	Rear Tires	20.8-38

TL2804G - 280hp

Engine: Diesel 6-cyl | Drive: 4x4 | Gearbox: 16F+8R Shift

DIMENSIONS & WEIGHT		PERFORMANCE	
Machine Weight	17,857 lbs (8,100 kg)	PTO Speed	540/1000 rpm
Overall Length	17.6 ft (5,350 mm)	Max Lift (610mm)	10,362 lbs (50.0 kN) at 610mm
Overall Width	7.2 ft (2,200 mm)	Min Turn Radius	≤ 20.3 ft (6.2 m) braking / ≤ 23.0 ft (7.0 m)
Overall Height	10.8 ft (3,300 mm)	Suspension	3-point type 3
Wheelbase	8.8 ft (2,668 mm)	Ground Clearance	16.7 in (425 mm)
TIRES			
Front Tires	16.9-28	Rear Tires	20.8-38